

泰燁用心、機械創新  
Passion & Innovation of Packaging...



Since 1977

泰燁機械有限公司  
TAYI YEH MACHINERY CO., LTD.

63048 雲林縣斗南鎮延平路三段191號  
No. 191, Sec. 3, Yenping Road, Dounan  
Township, Yunlin County 63048, Taiwan  
Tel: +886-5-5971156  
Fax: +886-5-5971159  
Email: tayiyeh@ms24.hinet.net



[www.tayi-yeh.com](http://www.tayi-yeh.com)



泰燁機械有限公司  
TAYI YEH MACHINERY CO., LTD.

Since 1977

收縮包裝機 SHRINK TUNNEL  
收縮包裝的完美展現 A Perfect Performance in Shrink Packaging



# POF/PE/PVC

## 收縮包裝機 Shrink Packaging Machine

### 特點 //

- 機台輸送速度及溫度，可依需求調整。
- 收縮爐內壁及內壁電熱相關配備皆為不銹鋼材質。
- 溫控系統具自動恆溫功能，收縮效能穩定。
- 電控元件、電機等，以日系或台製大廠牌為主。
- 規格化零組件，生產效率高，機械製程穩定。
- 機身採用粉體塗裝，美觀度佳。
- 機械鋼板為板金成型，骨架採用鋼材焊接，結構堅固。
- 可依收縮膜材質及包裝需求，設計、製造各系列機型。
- CE機型可依需求製造。

### Features //

- Adjustable shrinking speed and heating temp.
- Stable heating system for nice shrinking performance.
- Stainless steel components for inner tunnel related heating part.
- All spare parts are under standardize production.
- Machine frame made by steel material with powder painting for good durability.
- CE standard / Customized machines available upon request.

POF ▶ Polyolefin  
PE ▶ Polyethylene  
PVC ▶ Polyvinyl Chloride

◆ SA-313 POF  
循環式收縮機  
Circulation Type



◆ SA-316 POF  
循環式收縮機  
Circulation Type



◆ TY-50J POF  
噴射式收縮機  
Jet Type



◆ SA-318 PE-CC  
袖口式專用收縮機  
Apply with Sleeve  
Wrapping Machine



Make A Perfect Package  
with Shrinking Tunnel!

用途 / 適用收縮膜 Type / Film	循環式 / POF / 搭配L型封口機 Heat Circulation / Apply with L Type Sealer				噴射式 / POF Jet Type		搭配袖口式封口機 / PE Apply with Sleeve Wrapping Machine			
機械型號 Model	SA-313 POF	SA-316 POF	SA-317 POF	SA-318 POF	SA-319 POF	TY-50J POF	SA-317 PE	SA-318 PE	SA-319 PE	SA-321 PE
電壓 Power	3P 220V / 3P 380V / 3P 380V 4W 或依客戶需求 (upon request)									
耗電量 Consumption	9 KW	14 KW	19 KW	21 KW	24 KW	18 KW	26 KW	28 KW	33 KW	48 KW
機械尺寸 (長×寬×高) Overall Dim. (L×W×H)	1265×720×1220 mm	1865×720×1450 mm	1865×820×1500 mm	1865×880×1650 mm	2400×1060×1690 mm	2090×870×1590 mm	2800×960×1700 mm	2800×1060×1800 mm	2800×1160×1800 mm	3600×1440×1900 mm
收縮爐尺寸 (長×寬×高) Chamber (L×W×H)	800×400×200 mm	1200×400×250 mm	1200×500×300 mm	1200×600×350 mm	1500×700×400 mm	1500×500×300 mm	1500×500×350 mm	1500×600×450 mm	1500×700×450 mm	2000×900×500 mm
產品尺寸 (寬×高) Product (W×H)	300×130 mm	300×170 mm	390×220 mm	470×260 mm	550×300 mm	300×150 mm	350×250 mm	420×350 mm	490×350 mm	630×400 mm
輸送速度 (米/分鐘) Speed (m/min.)	0~7	0~8	0~8	0~8	0~8	0~8	0~8	0~8	0~8	0~8

\* 以上所有機型規格、形狀如有改變，恕不另行通知。 \* Specifications subject to change without prior notice.